

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 1

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

1. DESIGNATION OF THE MATERIAL OR MIXTURE AND COMPANY NAME

1.1 Product identifier

Product name Stainless steel spray Art. No. 151114
Trade name Stainless steel spray Art. No. 151114
CAS No.
EC No.

1.2 Relevant identified use of material or mixture and uses that are not advisable

Recommended
limitations of the
application

Use of the
material/mixture Technical aerosols

1.3 Details on the supplier who is making the safety data sheet available

Company Cimco Werkzeugfabrik Carl Jul. Müller GmbH & Co. KG
Hohenhagener Straße 1 - 5
D-42855 Remscheid, Germany
+49 (0) 21913718-01 Fax: +49 (0) 21913718-86

1.4 Emergency number **Emergency CONTACT (24-Hour-Number)**
GBK GmbH +49 (0)6132-84463

2. POSSIBLE HAZARDS

2.1 Classification of the material

- **Classification in accordance with the directive (EC) No. 1272/2008 [CLP/GHS]**
Aerosol 1 H222, H229,
Eye Irrit. 2 H319
STOT SE 3 H336
Aquatic Chronic 3 H412

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 2

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

2.2 Label elements

- **Labelling according to directive (EC) No. 1272/2008 [CLP/GHS]**



GHS02



GHS07

Signal word:

Hazard

Hazard warnings:

H222	Extremely inflammable aerosol.
H229	Pressurised container: could burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness and dizziness.
H412	Hazardous for water organisms, with long-term effects.

Safety information:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames as well as other sources of ignition.
P211	Keep away from ignition sources. Do not smoke.
P211	Do not spray against open flames or other sources of ignition.
P251	Do not puncture or incinerate, even after use.
P261	Avoid breathing in dust/smoke/gas/mist/vapour/aerosol.
P264	Wash hands thoroughly after use.
P271	Only use outdoors or in well ventilated rooms.
P273	Avoid releasing into the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection
P304 + P340	IN THE EVENT OF INHALATION: Move the person into fresh air and ensure they can breathe unrestrictedly.
P305 + P351 + P338	IN THE EVENT OF CONTACT WITH THE EYES: Rinse carefully with water for several minutes. Remove any contact lenses being worn if possible. Continue rinsing.
P312	In the event of feeling unwell, call the POISON CONTROL CENTRE/doctor.

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 3

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

P337 + P313	In the event of sustained eye irritation: Consult a doctor/seek medical attention.
P403 + P235	Store in a cool, well-ventilated place.
P405	Keep it locked away.
P410 + P412	Protect against direct sunlight and do not expose to temperatures above 50°C.
P501	Dispose of content/container as problem waste.

2.3 Other dangers

The product has a narcotic effect.

Results of the PBT and vPvB assessment

- **PBT:** The materials in the mixture do not meet the PBT/vPvB criteria according to REACH, Appendix XIII.
- **vPvB:** not applicable

3. COMPOSITION / INFORMATION ON COMPONENTS

Constituents	EC No.	CAS No.	Concentrate [% by weight]
Acetone	200-662-2	67-64-1	10 < 15 Flam. Liq. 2, H22 Eye Irrit. 2, H31 STOT SE 3, H336
Butane	203-448-7	106-97-8	20 < 25 Flam. Gas 1, H220 Compressed gas
Ethyl acetate	205-500-4	141-78-6	3 < 10 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Xylene	215-535-7	1330-20-7	5 < 10 Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315
Zinc oxide	215-222-5	1314-13-2	0.25 < 2.5 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Nickel powder	231-111-4	7440-02-0	0.25 - 0.99 Carc. 2, H351 STOT RE 1, H372 Skin Sens. 1, H317 Aquatic Chronic 3, H412

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 4

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

Naphtha (crude oil), heavy hydrogen-treated	265-150-3	64742-48-9	1 < 10 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066
Solvent naphtha (crude oil), slightly aromatic [NOTA P]	265-199-0	64742-95-6	2.5 < 10 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Aquatic Chronic 2, H411 STOT SE 3, H336 EUH066
Propane	200-827-9	74-98-6	20 < 25 Flam. Gas 1, H220 Compressed gas

4. FIRST AID MEASURES

4.1 Description of first aid measures

General information

Remove dirty, saturated clothing immediately.

After inhaling

Move the affected person into the fresh air and place in a resting position.
In the event of complaints, seek medical assistance.

After skin contact

In the event of skin contact, wash off with soap and water.
In the event of long-term skin irritation, consult doctor.

After swallowing

Do not induce vomiting
Seek medical attention if symptoms persist.

After eye contact

In the event of contact with the eyes, rinse thoroughly with lots of water and consult a doctor.

4.2 Important symptoms and effects which are acute or occur with a delay

Unconsciousness, state of intoxication, headache, confusion, dizziness

4.3 Indication of any immediate medical attention and special treatment needed

No information is available.

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 5

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

5. FIREFIGHTING MEASURES

5.1 Extinguishing agents

Suitable extinguishing agents Alcohol-resistant foam, extinguishing powder, carbon dioxide, sand

Unsuitable extinguishing agents Direct water jet

5.2 Particular risks associated with the material or mixture

Danger of bursting.
In the event of a fire, it is possible that hazardous gases may be formed.

5.3 Information on fire fighting

Special protective equipment for firefighting:

In the presence of combustion or carbonization gases, any firefighting, rescue and clearing up activities should be undertaken only with heavy-duty respiratory protection.

Further information:

Vapours are heavier than air and spread on the ground..
Collect contaminated quenching water separately; it must not enter the sewage system.

6. MEASURES IN THE EVENT OF ACCIDENTAL RELEASE

6.1 Person-related safety precautions, protective equipment and procedures to be followed in emergencies

Ensure sufficient ventilation.
Use personal protective clothing.
Keep ignition sources away.

6.2 Environmental protection measures

If surface water or sewage system are contaminated, inform the responsible authorities.
Do not allow to enter the sewage system or ground water.
Do not allow to enter sewage system / surface water / ground water.

6.3 Methods and material for containment and cleaning

Absorb with suitable liquid-binding materials.
Dispose of the absorbed material in accordance with the regulations.

Additional information

Sort out non-tight cans and dispose of according to regulations.

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 6

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

6.4 References to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protective equipment: see section 8

7. HANDLING AND STORAGE

7.1 Safety measures for safe handling

Information on safe handling

Ensure good room ventilation, extraction at the workplace where necessary.

General protection measures

Avoid contact with the eyes and skin.
Do not inhale gases / vapours / aerosols.

Hygiene measures

Do not smoke, eat, drink or sniff while working.
Wash hands before breaks and after finishing work.

Information on fire and explosion protection

Keep away from ignition sources – Do not smoke.
Together with air, vapours can form an explosive mixture.
Take measures to protect against electrostatic charges.

7.2 Conditions for safe storage taking incompatibilities into consideration

Storage requirements

The local authority regulations for storage of aerosol dispensers are to be observed.

Information on storage with other products

Further information on storage conditions

Protect against heat and direct sunlight.
The storage temperature must not exceed 50 °C.
Keep container in a cool, well-ventilated place.

Storage class

2B

7.3 Specific end use

See section 1.2

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 7

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

8. LIMITATION AND MONITORING OF EXPOSURE / PERSONAL PROTECTIVE EQUIPMENT

8.1 Limit values

CAS No.	Designation	Type	[mg/m ³]	[ppm]	Peak limit	Note
67-64-1	Acetone	8 hours	1200	500	2(I)	DFG,EU
106-97-8	Butane	8 hours	2400	1000	4(II)	DFG
141-78-6	Ethyl acetate	8 hours	1500	400	2(I)	DFG,Y
74-98-6	Propane	8 hours	1800	1000	4(II)	DFG
1330-20-7	Xylene (all isomers)	8 hours	440	100	2(II)	^DFG,EU,H

Occupational exposure limit values

CAS No.	Designation	Type	[mg/m ³]	[ppm]	Note
1330-20-7	Xylene, all isomers, pure	8 hours Briefly	221 442	50 100	skin
67-64-1	Acetone	8 hours	1210	500	

Additional information

National and local legal provisions must be adhered to.

8.2 Limiting and monitoring exposure

Personal protective equipment

General protective and hygiene measures

The usual regulations for handling chemicals needs to be adhered to.

Do not breathe in dust/smoke/mist. Keep away from food, drink and animal feed. Do not smoke, eat or drink while working. Avoid contact with the eyes and skin. Wash hands before a break and after finishing work.

Respiratory protection

If ventilation is inadequate, wear breathing apparatus. Briefly filtration device, filter AX/P2, otherwise breathing apparatus with independent air supply.

Hand protection

It is recommended to clarify the chemical resistance of the above-mentioned protective gloves for special applications with the glove manufacturer.

The type of chemical protection gloves is to be selected according to the concentration and quantity of hazardous materials at the specific workplace.

Eye protection

Tight fitting safety glasses

Personal protection

Protective workwear

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 8

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

Limiting and monitoring environmental exposure

Ensure good room ventilation, extraction at the workplace where necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on the basic physical and chemical properties

Form	aerosol
Colour	silver
Odour	solvent-like
Steam pressure	- na -
Relative density	- na -
Melting point / Freezing point	- na -
Explosive properties	- na -
Self-ignition temperature	- na -
Ignition point	- na -
Flammability	- na -
Oxidizing properties	- na -
Solubility in / miscibility with	- na -
Ignition temperature	- na -
Solvent content	- na -
Solids content	- na -

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 9

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

9.2 Other information

No information is available.

10. STABILITY AND REACTIVITY

10.1 Reactivity

No information available

10.2 Chemical stability

No information is available.

10.3 Possible hazardous reactions

No information is available.

10.4 Conditions to be avoided

Avoid exposure to heat.
Formation of explosive gas mixtures with air.

10.5 Incompatible materials

No information is available.

10.6 Dangerous decomposition processes

No decomposition when used as intended.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

	Value/Evaluation	Species	Method	Note
LD50 acute oral	1100 mg/kg		Conversion value	Xylene
LC50 acute for inhalation	>5 mg/l (4 h)		Conversion value	
Skin irritation	irritant			

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 11

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

12.6. Other harmful effects

Toxic for water organisms, plankton and fish.
Do not allow uncontrolled release of the product into the environment.
The product must not enter water systems.

13. INFORMATION ON DISPOSAL

Recommendation For correct waste disposal, empty the spray completely.
The waste category number/waste designation must be allocated according to EAKV and specifically for the industry and process.

Product Dispose of in accordance with local authority regulations.

Waste code 08 01 11* Paint and lacquer waste which contains organic solvents or other hazardous materials

Waste marked with an asterisk (*) are classed as hazardous waste according to Directive 2008/98/EC on hazardous waste.

Unclean packaging Dispose of in accordance with local authority regulations.

14. INFORMATION ON TRANSPORT

	ADR/RID	IMDG	IATA-DGR
14.1 UN number	1950	1950	1950
14.2 Proper UN shipping name	COMPRESSED GAS PACKAGING	AEROSOLS	Aerosols, inflammable
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packaging group	-	-	-
14.5 Environmental hazards	no	no	no

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 12

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

14.6 Special preventive measures for the user

Caution: Gases

14.7 Bulk transport according to Appendix II of the MARPOL agreement 73/78 and according to the IBC code

Not applicable

Transport by land ADR/RID

Danger label 2.1

Tunnel restriction code D

Classification code 5F

Transport as "Limited quantity" as per section 3.4 ADR

15. STATUTORY REGULATIONS

15.1 Regulations on safety, health and environmental protection / specific legal regulations for the material or the mixture

VOC guideline

VOC content 82.3%
VOC value 611g/L

National regulations:

Information on employment restrictions

The national laws regarding employment restrictions are to be observed.

Water hazard class 2 VwVwS Annex 4
Water-polluting

Incident ordinance: Incident ordinance, Annex I No. 8

15.2 Chemical safety assessment

A chemical safety assessment for materials in this mixture have not been carried out.

16. OTHER INFORMATION

Recommended use and restrictions

Existing national and local laws regarding chemicals are to be observed.

Nur für den gewerblichen Gebrauch. / For industrial use only.

**Safety data sheet pursuant to ordinance
(EC) No. 453/2010
(EC) No. 1907/2006 (REACH)**

Print date: 10.07.2015

page 13

Revised:10.07.2015

Cimco-Werkzeugfabrik
Carl Jul. Müller GmbH & Co. KG

Further information

National special provisions need to be implemented by each user on their own responsibility!
The information given is based on our current level of knowledge and serves to describe the product in terms of the safety precautions to be taken. It does not represent an assurance of properties of the product described.

Please pay attention to additional information! - Our safety data sheets have been prepared according to the valid EU guidelines WITHOUT taking into consideration any special national regulations regarding handling hazardous materials and chemicals.

EUH066	Repeated contact can cause rough or cracked skin.
H220	Extremely flammable gas.
H225	Liquid and vapour highly flammable.
H226	Liquid and vapour flammable.
H304	Can be fatal if swallowed or if material gets into respiratory tract.
H312	Hazardous to health upon skin contact.
H315	Causes skin irritation.
H317	Can cause allergic skin reactions.
H319	Causes serious eye irritation.
H332	Hazardous to health if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness and dizziness.
H351	Can probably cause cancer (state exposure method if conclusively verified that there is no danger with any other exposure method).
H372	Damages organs (state all affected organs) in the event of lengthy or repeated exposure (state exposure method if conclusively verified that this danger does not occur with any other exposure method).
H400	Extremely toxic for water organisms.
H410	Extremely toxic for water organisms, with long-term effects.
H411	Toxic for water organisms, with long-term effects.
H412	Hazardous for water organisms, with long-term effects.