



INSULATE SECURELY & FLEXIBLY

WITH HEAT-SHRINK TUBES

POLYOLEFIN HEAT-SHRINK TUBE

Thin-walled 2:1, assortments, halogen-free and flexible, flame-retardant (VW-1/UL 224)

Specifications:

Longitudinal shrinkage: < 5%

Continuous temperature: -55 to 125 °C

Shrinking temperature: 125 °C

Dielectric strength: 15 kV/mm (IEC 243)

Volume resistance: 1014 ohms x cm (IEC 93)

Tensile strength: 10.4 MPa (ASTM D2671)

Elongation at break: 200% (ASTM D2671)

HEAT-SHRINK TUBE SET "BLACK", IN A STURDY ASSORTMENT BOX

Diameter in mm before	after	Colour	Wall thickness in mm	Length in mm	Quantity/ Contents	Refill pack*	CIMCO-item no.
1.5	0.7	black	0.36	35.00	30	100 pcs.	18 1681
2.5	1.0	black	0.45	35.00	25	100 pcs.	18 1682
3.5	1.5	black	0.45	35.00	20	100 pcs.	18 1683
5.0	2.3	black	0.56	35.00	20	100 pcs.	18 1684
6.5	3.0	black	0.56	70.00	15	100 pcs.	18 1685
9.5	4.5	black	0.56	70.00	10	100 pcs.	18 1686
12.5	6.0	black	0.56	70.00	10	100 pcs.	18 1687
					130	1 box	18 1680




HEAT-SHRINK TUBE SET "COLOUR", IN A STURDY ASSORTMENT BOX

Diameter in mm before	after	Colour	Wall thickness in mm	Length in mm	Quantity/ Contents	Refill pack*	CIMCO-item no.
3.5	1.5	green/yellow	0.45	35.00	20	100 pcs.	18 1691
5.0	2.3	red	0.56	35.00	10	100 pcs.	18 1692
5.0	2.3	blue	0.56	35.00	10	100 pcs.	18 1693
5.0	2.3	green/yellow	0.56	35.00	10	100 pcs.	18 1694
9.5	4.5	red	0.56	70.00	10	100 pcs.	18 1695
9.5	4.5	blue	0.56	70.00	10	100 pcs.	18 1696
9.5	4.5	green/yellow	0.56	70.00	20	100 pcs.	18 1697
12.5	6.0	green/yellow	0.56	70.00	20	100 pcs.	18 1698
					110	1 box	18 1690



*Different sizes can also be ordered separately and as refills in plastic bags (100 pieces per bag).

OTHER HEAT-SHRINK TUBES



POLYOLEFIN HEAT-SHRINK TUBE


THIN-WALLED 2:1, BLACK, HALOGEN-FREE AND FLEXIBLE, FLAME-RETARDANT (VW-1/UL 224)



Diameter (mm)		Wall thickness	Version					
before	after	mm	Roll*		Box*		Piece*	
			L (m)	L (m)	L (m)	L (m)	L (m)	L (m)
1.1	0.5	0.33	18 1600	200	18 1610	12.00	-	-
1.5	0.7	0.36	18 1601	200	18 1611	12.00	-	-
2.5	1.0	0.45	18 1602	200	18 1612	11.50	18 1620	1
3.5	1.5	0.45	18 1603	200	18 1613	11.50	18 1621	1
5.0	2.3	0.56	18 1604	100	18 1614	9.50	18 1622	1
6.5	3.0	0.56	18 1605	100	18 1615	7.50	18 1623	1
9.5	4.5	0.56	18 1606	100	18 1616	6.50	18 1624	1
12.5	6.0	0.56	18 1607	100	18 1617	6.00	18 1625	1
19.0	9.0	0.70	18 1608	100	18 1618	5.00	18 1626	1
26.0	12.5	0.90	18 1609	50	18 1619	3.30	18 1627	1
31.5	15.0	1.00	-	-	-	-	18 1628	5
41.5	20.0	1.00	-	-	-	-	18 1629	5
50.0	25.0	1.00	-	-	-	-	18 1630	5
80.0	41.0	1.46	-	-	-	-	18 1631	5
100.0	51.0	1.46	-	-	-	-	18 1632	5

POLYOLEFIN HEAT-SHRINK TUBE

THIN-WALLED 2:1, COLOURS, HALOGEN-FREE AND FLEXIBLE, FLAME-RETARDANT (VW-1/UL 224)



Diameter (mm)		Wall thickness	Green/yellow		Red		Blue	
before	after	mm	Box*	L (m)	Box*	L (m)	Box*	L (m)
2.5	1.0	0.45	18 1640	11.50	18 1660	11.50	18 1670	11.50
3.5	1.5	0.45	18 1641	11.50	18 1661	11.50	18 1671	11.50
5.0	2.3	0.56	18 1642	9.50	18 1662	9.50	18 1672	9.50
6.5	3.0	0.56	18 1643	7.50	18 1663	7.50	18 1673	7.50
9.5	4.5	0.56	18 1644	6.50	18 1664	6.50	18 1674	6.50
12.5	6.0	0.56	18 1645	6.00	18 1665	6.00	18 1675	6.00
19.0	9.0	0.70	18 1646	5.00	18 1666	5.00	18 1676	5.00
26.0	12.5	0.90	18 1647	3.30	18 1667	3.30	18 1677	3.30
			Piece*					
41.5	20.0	1.00	18 1648	5	-	-	-	-
50.0	25.0	1.00	18 1649	5	-	-	-	-
80.0	41.0	1.46	18 1650	5	-	-	-	-
100.0	51.0	1.46	18 1651	5	-	-	-	-

POLYOLEFIN HEAT-SHRINK TUBE

THIN-WALLED 2:1, TRANSPARENT, HALOGEN-FREE AND FLEXIBLE, NOT FLAME-RETARDANT (VW-1/UL 224)



Diameter (mm)		Wall thickness	Transparent	
before	after	mm	Box*	L (m)
2.5	1.0	0.45	18 4250	11.50
3.5	1.5	0.45	18 4251	11.50
5.0	2.3	0.56	18 4252	9.50
6.5	3.0	0.56	18 4253	7.50
9.5	4.5	0.56	18 4254	6.50
12.5	6.0	0.56	18 4255	6.00
19.0	9.0	0.70	18 4256	5.00
26.0	12.5	0.90	18 4257	3.30

POLYOLEFIN HEAT-SHRINK TUBE

THIN-WALLED 3:1, BLACK, HALOGEN-FREE AND FLEXIBLE, FLAME-RETARDANT (VW-1/UL 224)



Diameter (mm)		Wall thickness	Version			
before	after	mm	Box*		Piece*	
			L (m)	L (m)	L (m)	L (m)
1.5	0.5	0.45	18 4260	15	-	-
3.0	1.0	0.65	18 4261	10	-	-
6.0	2.0	0.65	18 4262	10	-	-
9.0	3.0	0.75	18 4263	8	-	-
12.0	4.0	0.75	18 4264	5	-	-
18.0	6.0	0.85	18 4265	5	-	-
24.0	8.0	1.00	18 4266	5	-	-
39.0	13.0	1.50	-	-	18 4267	1
50.0	16.0	2.50	-	-	18 4268	1
80.0	26.0	2.60	-	-	18 4269	1
100.0	33.0	2.60	-	-	18 4270	1

POLYOLEFIN HEAT-SHRINK TUBE

THIN-WALLED 3:1, BLACK, HALOGEN-FREE AND FLEXIBLE, FLAME-RETARDANT (VW-1/UL 224), WITH INTERNAL ADHESIVE



Diameter (mm)		Wall thickness	With internal adhesive	
before	after	mm	Piece*	L (m)
3.2	1.0	0.55	18 4280	1.22
6.4	2.2	0.80	18 4281	1.22
9.5	3.2	0.90	18 4282	1.22
12.7	4.2	1.20	18 4283	1.22
19.1	6.3	1.40	18 4284	1.22
25.4	8.5	1.50	18 4285	1.22
39.0	13.5	1.90	18 4286	1.22
50.0	17.0	2.10	18 4287	1.22

Specifications and additional information

