

OVERSTOCK LIST 2020

PROMOTION
valid until 31.12.2020

In preparation for the upcoming end of the year we have checked our stock for you. We have excess stock of the following products, so you can now benefit from our price reductions of up to 60 %.

Ask your electrical
wholesaler for offers!

LED construction site spotlight 10 W

For every mobile application, also outdoors (protection class: IP 65) due to large lithium-ion batteries (7.4 V/2,260 mAh), battery operating time: 4 hours, battery charging time: 3 hours, luminous flux: 700 Lumen, luminous colour: 5,500 – 6,000 K, radiation angle: 120°, state-of-the-art LED technology enables precise illumination in a horizontal and vertical orientation, overcharge and discharge protection, solid die cast aluminium housing, toughened glass.

CIMCO-item no. 11 1580



LED construction site spotlight 20 W

For every mobile application, also outdoors (protection class: IP 65) due to large lithium-ion batteries (7.4 V/6,600 mAh), battery operating time: 5 hours, battery charging time: 5 hours, luminous flux: 1,300 Lumen, luminous colour: 5,500 – 6,000 K, radiation angle: 120°, state-of-the-art LED technology enables precise illumination in a horizontal and vertical orientation, overcharge and discharge protection, solid die cast aluminium housing, toughened glass.

CIMCO-item no. 11 1586



LED construction site spotlight 30 W

For every mobile application, also outdoors (protection class: IP 65) due to large lithium-ion batteries (14.8 V/6,600 mAh), battery operating time: 3 hours, battery charging time: 5 hours, luminous flux: 2,000 Lumen, luminous colour: 5,500 – 6,000 K, radiation angle: 120°, state-of-the-art LED technology enables precise illumination in a horizontal and vertical orientation, overcharge and discharge protection, solid die cast aluminium housing, toughened glass.

CIMCO-item no. 11 1588



LED construction site spotlight 50 W

For every mobile application, also outdoors (protection class: IP 65) due to large lithium-ion batteries (14.8 V/6,600 mAh), battery operating time: 3 hours, battery charging time: 5 hours, luminous flux: 2,600 Lumen, luminous colour: 5,500 – 6,000 K, radiation angle: 120°. state-of-the-art LED technology enables precise illumination in a horizontal and vertical orientation, overcharge and discharge protection, solid die cast aluminium housing, toughened glass.


CIMCO-item no. 11 1590



LED construction site spotlight 20 W with spare rechargeable battery

For every mobile application, also outdoors (protection class: IP 65) due to large lithium-ion batteries (7.4 V/6,600 mAh), battery operating time: 3 hours, battery charging time: 5 hours, luminous flux: 1,300 Lumen, luminous colour: 5,500 – 6,000 K, radiation angle: 120°, including spare rechargeable battery, CIMCO-item no. 11 1593, special feature: the USB port with lockable cover can be used to charge mobile devices such as smartphones or tablets. State-of-the-art LED technology enables precise illumination in a horizontal and vertical orientation, overcharge and discharge protection, solid die cast aluminium housing, toughened glass.

CIMCO-item no. 11 1592



LED work lamp

With 60 (tube light) plus 9 (torch light) white LEDs, the lamp wins acclaim due to its high yield of bright, even and focused light, simple operation with just one push button switch, unlimited freedom of movement thanks to cordless operation with integrated rechargeable battery (7.2 V NiMH), can be charged with 230 Volt/50 Hz battery charger and 12-volt cigarette lighter (charging time approx. 1.5 hours), very low power consumption for a long light duration (approx. 5 to 8 hours, depending on mode), shock-resistant, oil, splash and dust-proof housing (IP 54) made of polycarbonate with a non-slip rubber handle, handy and light: length 410 mm, ø 41 mm, weight 470 g.

CIMCO-item no. 11 1522



AS LONG AS STOCKS LAST!

cimco[®]
W E R K Z E U G F A B R I K

LED PEN lamp

Can be switched from surface illumination to point illumination (torch), wide area illumination in pocket format, housing made from ABS material, rechargeable Li-Ion battery, with attachment clip for shirt pocket and/or trouser pockets, 2 magnets ensure secure hold to metallic objects, including USB charging cable.



CIMCO-item no. 11 1524

T-handle screwdriver set, 8-piece

For applying significantly more force than conventional screwdrivers, with double-sided drive for hex socket screws (allen screws), voluminous, edge-free handle in 2-component technology with soft rubber insert, blades made of tempered S2 special steel, chrome-plated, with ball-end on longer blade, black satined, including a practical storage stand for on the workbench or mounting on the wall.
One key each of 2 – 2,5 – 3 – 4 – 5 – 6 – 8 – 10 mm.



CIMCO-item no. 11 0520

Aluminium telescopic ladder X-TEND

Telescopic ladder complying with European Standard EN 131 for professional use in the fields of trade and industry. By simply pulling out the ladder bars from rung to rung, the height of the ladder can be varied as desired and can be fixed in the desired position by means of the self-locking safety buttons. After use, the conductor retracts automatically by pressing the locking buttons. Extremely compact in the transport state (only 80 cm high), can be extended to a maximum height of 3.80 metres, manufactured from abrasion-resistant anodised aluminium, 13 rungs with a width of 40 mm and an anti-slip profile for comfortable and safe working, rung distance of 30 cm, lower ladder beam diameter of 8 cm, 49 cm wide floor beam complete with anti-slip plastic feet, max. load-bearing capacity of 150 kg, weight only 11.5 kg.



CIMCO-item no. 14 6720

Aluminium telescopic ladder X-TEND PLUS

The further development of the X-TEND telescopic ladder sets new standards for the user. Manufactured according to European Standard EN 131, can be used as a leaning ladder with a height of 2 metres and as a step ladder with a height of 1.70 metres, the two last rungs (0.60 metres) additionally serve as a safety function for leaning or securing, also ideal for use on stairs. Thanks to the telescopic function, the conductor can be stored in the most confined of spaces and increases carrying comfort. 5 rungs with a width of 40 mm and an anti-slip profile for comfortable and safe working, rung distance of 30 cm, max. load-bearing capacity of 150 kg, weight only 19.3 kg.



CIMCO-item no. 14 6722

remaining stock: 2 pieces

Warning vest “2 m distance”

Produced acc. to EN ISO 20471/class 2, TÜV Rheinland approved, size variably adjustable with 2 Velcro straps, two reflective strips, 100 % polyester, size: approx. 68 x 66 cm



CIMCO-item no. 14 2000

Cable shears

With lever transmission and interchangeable cutter heads, PVC-covered tubular steel shanks



CIMCO-item no. 12 0150

Digital Multimeter

Low-Batt display, resistance, diode test and acoustic continuity test, standard measurement ranges V/DC, V/AC, A/DC, A/AC, CAT III 600 V



CIMCO-item no. 11 1408

Cable knife set

Cable knife with bracket system, adjustable inner knife for longitudinal and circular cut, protected hook blade with adjustable depth, automatic protection mechanism. Included interchangeable bracket sizes: 4 – 16 mm Ø, 8 – 28 mm Ø, 27 – 35 mm Ø, 35 – 50 mm Ø, 50 – 70 mm Ø. In high-quality raaco plastic box.



CIMCO-item no. 12 2018

Ask your electrical
wholesaler for offers!

AS LONG AS STOCKS LAST!

WET.PROTECT

Protects against wet and moisture-related short circuits, failure and corrosion, infiltrates the moisture and subsequently forms a durable protective film, maintains conductivity and increases the service life of the treated parts, can be used as a preventive measure or directly following the effects of moisture as a means of repair. Only handle when in a de-energised state. Caution: Labeling in Italian! Size: 200 ml.

CIMCO-item no. 15 9900



PTFE-Spray

A dry, clean, grease-free, highly-adhesive and durable dry lubricant. Repels dirt, dust and water. Resistant to corrosive chemicals and oils. Temperature-resistant from -180 °C to +250 °C. Size: 400 ml.

CIMCO-item no. 15 1002



Super 4 wire stripper

SUPER 4 wire stripper with the cross section range of 0,5 to 4 mm²

CIMCO-item no. 10 0760 loosely packed without packaging



PowerGRIP plier wrench, 300 mm

Parallel gripping pliers with practical push-button adjustment, easy-running fine adjustment, chrome-plated with dip insulated handles.

CIMCO-item no. 10 1243 Span: 60 mm



Cable cutter for steel cables

One hand actuation due to optimal handle design, 2-component handles, blade hardness 60 – 62 HRC, suitable for cutting flexible steel cables up to ø 5 mm.

CIMCO-item no. 12 0146



Professional lightweight metal spirit level

Computer-optimized profile (COP), two integrated acrylic vertical levels with Plumb-Site® Dual-View™, a larger horizontal level, with finely milled surfaces on both sides, ergonomic grips with patented Ergo Grip™ anti-slip function, polypropylene and TPR end caps with air sprung PVC shock absorbers. Accuracy: 0.5 mm / m.

CIMCO-item no. 21 1530



Professional digital magnetic spirit level

Plumb-Site® Dual-View™ level, acrylic glass block levels, Ergo Grip™ handles, LCD display at a 45° angle with backlighting, does not turn when the spirit level is turned, HOLD function, MODE function degree/percent/angle, Re-calibration function and "False Zero", Memory recall for up to 9 measurements, 9 V-battery with charge display, length: 60 cm, weight: 686 g.

CIMCO-item no. 21 1532



Professional digital magnetic spirit level with laser pointer

Plumb-Site® Dual-View™ level, acrylic glass block levels, Ergo Grip™ handles, LCD display at a 45° angle with backlighting, does not turn when the spirit level is turned, HOLD function, MODE function degree/percent/angle, Re-calibration function and "False Zero", memory recall for up to 9 measurements, 9 V-battery with charge display, laser pointers align the angle of the spirit level to a remote point up to 50 m away, 1/4" thread in bottom of housing to easily mount it on a tripod, length: 60 cm, weight: 740 g

CIMCO-item no. 21 1534



Electrician's safety spirit levels, 600 mm

With three levels (1 x horizontal, 1 x vertical, 1 x 45°), made of non-conductive, distortion-free plastic with ergonomic recessed grips and a patented level housing.

CIMCO-item no. 21 1536



cimco®

FLEXI-CRIMP front crimping pliers

With web or lamella die that self-adjusts to the conductor cross-section, square crimp with 16 mm crimp length, rounded inner edges so as not to cut into thin-walled wire end ferrules, front crimping, i.e. the connectors and conductors are inserted into the tool from the front, making it suitable for work in hard access places and confined spaces, with innovative precision steel spring component for constant crimping quality even at extremely high or low temperatures, adjustable via cam, unlockable forced locking, ergonomically shaped two-component handles with soft padding.

Cross section range: 0,14 – 6 mm²

CIMCO-item no. 10 1940

Ask your electrical
wholesaler for offers!



PROMOTION
valid until 31.12.2020

Automatic crimping tool for wire end ferrules

Front insertion of ferrule, trapezoid crimp, cross section range 0,14 - 6 mm²

CIMCO-item no. 10 4190



JUMBO tool case

Extremely voluminous tool case, perfect for carrying tools, electrical machines and components simultaneously, made of unbreakable, impact-resistant and shock-proof HDPE plastic, with multiple rivets and exceptionally strong aluminium frame, simple and comfortable to transport thanks to 2-step pull-out telescopic handle and large rollers with ball bearings, 2 removable click system tool boards with innovative, patented FLEXIPOUCH pockets, 1 document compartment, 2 robust lockable snap locks, 2 hinged carrying handles for optional vertical or horizontal transport, 4 rubber bottom-sliders.

Dimensions (L x W x H): 415 x 500 x 360 mm

CIMCO-item no. 17 0072



Tool bag textil/woven fabric

Made of hard-wearing plastic fabric, bag cover with additional reinforcement, for even distribution of the load, 4 strong plastic floor sliders make sure it is stable, the water and dirt resistant plastic coating on the bottom makes it easy to clean, additional elastic straps on the lid, numerous tool insertion straps, trolley holder and business card holder on the back, practical tool segments to flexibly hold tools on the middle wall, lateral loops for the shoulder straps (included in the scope of delivery), opening function 30° and 90° (side walls), weight: 4,2 kg

Dimensions (L x W x H): 400 x 470 x 270 mm

CIMCO-item no. 17 0940



Tool case Bomber

Double-walled hardshell case made of impact-resistant and shock-proof polyethylene plastic. Extremely durable, virtually indestructible. Resistant to high and low temperatures and also to many chemicals. With 2 tool boards, 2 lockable clamp locks, document compartment, adjustable partitions in bottom of case. Weight: 5,5 kg

Dimensions (L x W x H): 360 x 475 x 205 mm

CIMCO-item no. 17 0076



AS LONG AS STOCKS LAST!

www.cimco-international.com

Technical modifications, colour deviations, price changes, errors and misprints reserved. Offer only valid while stocks last. All prices are valid until 31.12.2020 and are quoted exclusive of statutory VAT – Sale only via specialist wholesalers.

cimco[®]
W E R K Z E U G F A B R I K